

STI Wireless Alert Series



STI-34400



PRODUCT OVERVIEW

The Wireless Alert Series wirelessly monitors up to 4 or 8 different STI devices at a single, convenient location. The receivers will chime and flash when a monitored transmitter is triggered, alerting users to the happenings in their home/building. Supervised for low battery and signal reception, they operate up to 1000' (line of sight). Monitor: open/closed garage door, mail delivery, car in the driveway, open exit door, removed fire extinguisher, fence gate, medicine cabinet, etc. All models include a 4-Channel Receiver.

HOW IT WORKS

Wireless Driveway Monitor – Solar or Battery Powered (STI-34100 or STI-34150)

Detects when a vehicle enters or leaves a driveway. Movement of any large metallic (iron or steel) object close to the driveway sensor will transmit a signal to the included receiver.

Wireless Mailbox Alert (STI-34200)

When a mailbox door is opened, the included receiver will alert, eliminating repeat trips to an empty mailbox.

Wireless Garage Sentry® Alert (STI-34300)

Included receiver alerts when garage door is opened and provides an open or closed door status.

Wireless Universal Alert (STI-34400)

Universal Alert will let you know if the monitored site is tripped. A wireless signal is sent to the included receiver. Can be used on a medicine cabinet, fence gate, window, shed, etc.

Wireless Doorbell Button Alert (STI-34600)

Water/weather resistant button sends a wireless signal to the receiver when pressed. Operates up to 500' (line of sight).

Wireless Motion Detector Alert – Indoor or Outdoor (STI-34700 or STI-34750)*

When sensor detects movement in a monitored area, a wireless signal is sent to the included receiver. To conserve battery, when sensor is tripped it will not activate for three minutes.

FEATURES

- Wirelessly monitor up to 4 or 8 different devices and know what is happening in your home/building.
- Receivers will chime and flash, alerting a monitored site has been tripped.
- Operates up to 1000' (line of sight) range between transmitters and receivers. STI-34600 offers 500 foot line of sight range.
- Includes battery.
- Supervised for low battery and signal reception.
- Installation options include: an on board reed switch, set of terminals (remote) or as a tilt switch (excludes Wireless Driveway Monitors).
- Includes a magnetic contact with 18" lead for irregular installations.
- Easy installation.

STI Wireless Alert Series

Dimensions and Technical Information

MODELS AVAILABLE (Includes 4-Channel Receiver)

STI-34100	Wireless Driveway Monitor (solar powered)
STI-34150	Wireless Driveway Monitor (battery powered)
STI-34200	Wireless Mailbox Alert
STI-34300	Wireless Garage Sentry Alert
STI-34400	Wireless Universal Alert
STI-34600	Wireless Doorbell Button Alert
STI-34700	Wireless Indoor Motion Detector Alert
STI-34750	Wireless Outdoor Motion Detector Alert

Accessories

STI-34104	4-Channel Receiver
STI-V34104	4-Channel Voice Receiver
STI-34108	8-Channel Receiver
STI-34101	Driveway Monitor (solar powered) Sensor
STI-34151	Driveway Monitor (battery powered) Sensor
STI-34201	Mailbox Alert Sensor
STI-34301	Garage Sentry Sensor
STI-34401	Universal Alert Sensor
STI-30105	Extended antenna
STI-34106	Key Fob
STI-34109	Repeater

Other Wireless Products Available

STI-34100	Wireless Driveway Monitor (solar powered) and 4-Channel Receiver
STI-34150	Wireless Driveway Monitor (battery powered) and 4-Channel Receiver
STI-6200WIR4	Wireless Fire Extinguisher Theft Stopper® with 4-Channel Receiver
STI-6400WIR4	Wireless Exit Stopper® with 4-Channel Receiver
STI-6517B	Wireless Stopper® Station Shield with sound and transmitter

APPROVALS

TESTING

- FCC & IC Compliant



**Safety Technology
International, Inc.**

2306 Airport Road
Waterford, Michigan
48327, USA

Tel: 248-673-9898
Fax: 248-673-1246
Toll-free: 800-888-4784
info@sti-usa.com
www.sti-usa.com

Unit 49G Pipers Road
Park Farm Industrial Estate
Redditch, Worcestershire
B98 0HU England

Tel: 44 (0) 1527 520 999
Fax: 44 (0) 1527 501 999
Free: 0800 085 1678 (UK)
www.sti-europe.com